

MODEL NO.	VERTICAL STROKE	CROSSWISE STROKE	TRAVERSE STROKE	DRY CYCLE TIME(S)	SIDE-POSE ROTATION ANGLE(DEGREE)	MAX PAYLOAD(I NCL.JIG) KG	DRIVE MODE	TAKE-OUT TIME(S)	ROBOT SIZE L*W*H (MM)	APPLICABLE TO IMM(TONNAGE)	SERVO MOTOR(AXIS)	REMARKS
RHD700IS	700	170	1300	8	90	3	Z-SERVO	1.7	2000*1300*1425	80-150T	1	
RHD800IS	800	170	1300	8.5	90	3	Z-SERVO	1.9	2000*1300*1515	150-200	1	
RHD800WS	800	250	1300	10	90	4	Z-SERVO	1.8	2000*1300*1250	150-200	1	
RHD900WS	900	250	1550	11	90	5	Z-SERVO	1.9	2230*1300*1320	200-320	1	
RHD1100WS	1100	250	1750	11	90	5	Z-SERVO	2.2	2410*1420*1420	320-400	1	
RQ700IS-S2	700	170	1300	8	90	3	Z/Y-MAIN ARM SERVO	1.7	2000*1300*1425	80-150T	2	
RQ800IS-S2	800	170	1300	8.5	90	3	Z/Y-MAIN ARM SERVO	1.9	2000*1300*1515	150-200	2	
RQ800WS-S2	800	250	1300	10	90	4	Z/Y-MAIN ARM SERVO	1.8	2000*1300*1250	150-200	2	
RQ900WS-S2	900	250	1550	11	90	5	Z/Y-MAIN ARM SERVO	1.9	2230*1300*1320	200-320	2	
RQ1100WS-S2	1100	250	1750	11	90	5	Z/Y-MAIN ARM SERVO	2.2	2410*1420*1420	320-400	2	
RQ700IS-S3/S5	700	560	1300	7~9	90	3	Z/Y/X MAIN ARM SERVO	1.3	2500*1400*1435	50-150	3~5	
RQ800IS-S3/S5	800	680	1400	7~8	90	5	Z/Y/X MAIN ARM SERVO	1.4	2155*1590*1620	150-200	3~5	
RQ900IS-S3/S5	900	750	1520	7.5~10	90	5	Z/Y/X MAIN ARM SERVO	1.8	2280*1650*1740	200-320	3~5	
RQ700WS-S3/S5	700	560	1300	6~8	90	3	Z/Y/X MAIN ARM SERVO	1.3	2500*1400*1205	50-150	3~5	
RQ800WS-S3/S5	800	660	1400	6~9	90	5	Z/Y/X MAIN ARM SERVO	1.6	2155*1590*1380	150-200	3~5	
RQ900WS-S3/S5	900	690	1520	7~10	90	5	Z/Y/X MAIN ARM SERVO	1.8	2280*1650*1440	200-320	3~5	
RQ1200WS-S3/S5	1200	800	1700	8.5~11	90	5	Z/Y/X MAIN ARM SERVO	2	2480*1760*1560	320-550	3~5	
RN1100WS-S3	1100	500	1550	4.2	90	7	SINGLE ARM ALL SERVO DRIVEN	0.9	2790*1430*1550	300-380	3	
RN1300WS-S3	1300	800	2180	5.5	90	10	SINGLE ARM ALL SERVO DRIVEN	1.2	3500*1940*1830	380-450	3	
RN1500WS-S3	1500	1200	2420	6.8	90	10	SINGLE ARM ALL SERVO DRIVEN	2	3740*2060*1950	450-650	3	

RN1700WS-S3	1700	940	2500	16	90	15	SINGLE ARM ALL SERVO	3	3800*2540*2 245	650-800	3	
RN2000WS-S3	2000	1300	2900	18	90	25	SINGLE ARM ALL SERVO	3	4250*2700*2 480	800-1200	3	
RN2500WS-S3	2500	1650	3700	20	90	30	SINGLE ARM ALL SERVO DRIVEN	3.5	5200*3200*2 800	1200-2000	3	
RN3000WS-S3	3000	1750	4200	22	90	30	SINGLE ARM ALL SERVO DRIVEN	3.5	5700*3700*3 100	2000-3000	3	
RG900WS-S3	900	450	1640	3.8	90	3	SINGLE ARM ALL SERVO DRIVEN	0.8	2350*1515*1 335	220-320	3	
RG1200WS-S3	1200	450	1640	4	90	3	SINGLE ARM ALL SERVO DRIVEN	0.9	2350*1515*1 460	320-550	3	
RX650	650	120	N/A	4.2/4.0	N/A	2	PNEUMATIC	0.9/0.7	N/A	50-180	N/A	SPRUE PICKER
RL650	650	120	N/A	4	N/A	2	PNEUMATIC	0.7	N/A	50-180 for vertical machine	N/A	SPRUE PICKER